

FCW1500 Square - INSTALLATION INSTRUCTIONS

CAUTION: BEFORE CONNECTING THE FIXTURE TO A POWER SUPPLY, MAKE SURE THE POWER IS SWITCHED OFF.

Up/Down Fixture



FC
LIGHTING

t 800.900.1730 f 630.889.8106
3609 Swenson Ave. St. Charles, IL 60174

DETAILED ILLUSTRATIONS

GENERAL:

1. Before starting the installation, make sure all electricity has been turned off and electrical breaker has been locked out and tagged out.
2. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
3. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code.
4. These fixtures are intended to be mounted to a J-Box directly supported by the building structure.

NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur.

INSTALLATION

1. Remove Front Plate from the Back of Fixture.
2. Attach both AC 3-Wire Starter Cables from the fixture coming through the sealed center Cord Management Area to the source with all connections inside the J-Box area.
IMPORTANT: Make sure all connections follow code requirements.
3. Mount level fixture to J-Box with holes provided.
Ensure Gasket is snug between fixture and mounting surface to seal properly.
NOTE: Check fixture is level before tightening.

4. Lastly, re-attach the Front Plate to the fixture.

IMPORTANT: All FC|SSL products can be cleaned with non-abrasive and chemical free agents. Use a soft cloth with mild detergent on exterior only.

