FCW1011, EXTERIOR SURFACE DOWNLIGHT — INSTALLATION INSTRUCTIONS

CAUTION: BEFORE CONNECTING THE LUMINAIRE TO A POWER SUPPLY, MAKE SURE THE POWER IS SWITCHED OFF.

OUTDOOR LIGHTING

www.fclighting.com 3609 Swenson Ave. St. Charles, IL 60174

DETAILED ILLUSTRATION

GENERAL:

- Before starting the installation, make sure all electricity has been turned off and electrical breaker has been locked out and tagged out.
- To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
- All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code.
- These luminaires are intended to be mounted directly to the building structure, over the electrical junction box or conduit outing.
- 5. All luminaires to be installed by a qualified electrician.


NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur.


INSTALLATION:

- Use a 9/64" Hex tool to remove the four screws located on either side of the luminaire. Place the screws in a safe location. (Figure 1)
- 2. Carefully remove the front cover from the luminaire. (Figure 2)
- Affix the backplate to the wall. Installers can either affix via surface-mounting holes or attach directly to the junction box. (Figure 3)

NOTE: Use Junction Box mounting screws (6-32, third-party hardware) to secure the mounting plate to the Junction Box on the intended Surface.

WARNING: LED lamping is integral and NOT intended for general servicing. Luminaire is designed to work with standard size J-boxes, sizes may vary.





FCW1011, EXTERIOR SURFACE DOWNLIGHT — INSTALLATION INSTRUCTIONS

CAUTION: BEFORE CONNECTING THE LUMINAIRE TO A POWER SUPPLY, MAKE SURE THE POWER IS SWITCHED OFF.

OUTDOOR LIGHTING

www.fclighting.com 3609 Swenson Ave. St. Charles. IL 60174

DETAILED ILLUSTRATION

GENERAL:

- Before starting the installation, make sure all electricity has been turned off and electrical breaker has been locked out and tagged out.
- To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
- All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code.
- These luminaires are intended to be mounted directly to the building structure, over the electrical junction box or conduit outing.
- 5. All luminaires to be installed by a qualified electrician.

NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur.

INSTALLATION:

- 4. Feed power and dimming wires through backplate, connect wires to luminaire. (Figure 4)
 - Black Line
 - White Neutral
 - Green Ground
 - Purple Dim+
 - Pink Dim-
- Replace the cover the backplate and secure to wall using a 9/64" Hex tool. When fastening security screws, tighten to 20 in-lbs. (Figure 5)
- 6. Installer MUST add a bead of silicon where back edge of luminaire housing meets the mounting surface. (Figure 6)

WARNING: LED lamping is integral and NOT intended for general servicing. Luminaire is designed to work with standard size J-boxes, sizes may vary.

